

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. INTL-0033-US (P5395)

Total Pages in this Submission 24

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application Washington, D.C. 20231

Transmitted herewith for filing under	35 U.S.C. 111(a) and 37 C.F.R. 1	53(b) is a new utility patent application for an
invention entitled:	2. 2. 2. 2. 2. 1. 1(a) and 07 0.1 .1(. 1.	os(b) is a new utility patent application for an
Transfer StrateGu.		

inven	ition	entitle	ed:	1 for 1	illing under 3:	5 U.S	S.C. 111(a) and 37 C.F.R. 1.53	3(b) is a new utility patent application for an
P	BINA!	RYC	COMP.	ATIF	BLE SOFTW.			
		ited by	-					
	Kenn	ieth S	S. Knaj	pton,	, 111			
lf a ('NOC		ATIO	N AP	PLICATION,		eck appropriate box and supply	the requisite information:
	Cont	tinua	ition				Continuation-in-part (CIP)	
2227	ch is a		41-m		7: : :al			
. ===	Cont h is a	tinuat a:	tion	L	Divisional		Continuation-in-part (CIP)	of prior application No.:
		a: tinua(ition		Divisional		Continuation-in-part (CIP)	of prior application No.:
Emclo	osed a	аге:						
— ∏							Application Elements	
(1) (1) (1) (1)	X	Filir	ng fee	as c	alculated and	d tran	insmitted as described below	
<u>u</u> 12.	\boxtimes	Spe	ecificat	tion h	having		pages and in	ncluding the following:
	. a.	×	Desc	criptiv	ve Title of the			
	b.		Cros	s Re	ferences to F	Relate	ted Applications (if applicable)	
	C.						erally-sponsored Research/Dev	velopment <i>(if applicable</i>)
	d.						ppendix (if applicable)	responsible to approximately
	e.	×			and of the Inve			
	f.	\boxtimes			nmary of the Ir			
	g.	×			-		awings (if drawings filed)	
	h.	X			Description			
	i.	\boxtimes	Claim	n(s) e	as Classified E	Belov	ow .	
	j.				of the Disclosu			

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. INTL-0033-US (P5395)

Total Pages in this Submission 24

_				Application Elements (Continued)
3.	. 🛚	Dra	awing(s) (when neces	ssary as prescribed by 35 USC 113)
	a.	. 🗵	Formal	Number of Sheets3
	b.	. 🗆	Informal	Number of Sheets
4.	. 🛚	Oaf	ath or Declaration	
	a.	. 🛛	Newly executed (ori	riginal or copy)
	b.	. 🗇	Copy from a prior ar	application (37 CFR 1.63(d)) (for continuation/divisional application only)
	C.	. 🗵	With Power of Attorn	
	d.		<u>DELETION OF INVI</u> Signed statement at see 37 C.F.R. 1.63(attached deleting inventor(s) named in the prior application
0		The Box	e entire disclosure of t	nce (usable if Box 4b is checked) the prior application, from which a copy of the oath or declaration is supplied under as being part of the disclosure of the accompanying application and is hereby be therein.
≟6. ≟		Con	mputer Program in Mic	icrofiche (Appendix)
		Nuc	leotide and/or Amino	Acid Sequence Submission (if applicable, all must be included)
			Paper Copy	
) N	b.		Computer Readable	e Copy (identical to computer copy)
- 7. 	C.			Identical Paper and Computer Readable Copy
₽,				Accompanying Application Parts
8.	×	Assi	ignment Papers (coνε	er sheet & document(s))
9.		37 C	CFR 3.73(B) Statemer	ent (when there is an assignee)
10.		Engl	lish Translation Docun	ment (if applicable)
11.		Infor	rmation Disclosure Sta	tatement/PTO-1449
12.		Preli	iminary Amendment	
13.	\boxtimes /	Ackn	nowledgment postcard	'd
14.	⊠ (Certif	ificate of Mailing	
	ſ	□ F	First Class 🗵 Ex	xpress Mail (Specify Label No.): F1.1382689731'S

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. INTL-0033-US (P5395)

Total Pages in this Submission 24

			A	accompanying Ap	plication P	'arts (Co	ntinued)	
15.		Certified C	copy of Priority	y Document(s) (if fo	əreign priori	ty is clain	ned)	
16.		Additional	Enclosures (p	please identify below	w):			
		l						
		: !						
				Fee Calculat	tion and T	ansmitta	al	
				CLAIMS A	S FILED			
	For		#Filed	#Allowed	#Extra		Rate	Fee
Total C			17	- 20 =	0	x	\$22.00	\$0.00
Indep.			4	- 3 =	1	×	\$82.00	\$82.00
	e Dep	endent Ci	laims (check i	if applicable)]			\$0.00
T.								
OTHE	Stress (Specify purpose) \$0.00						\$0.00	
							TOTAL FILING FEE	\$872.00
⊠´Ac		in the amo		872.00 to co	over the filing	g fee is e	nclosed.	<u> </u>
⊠ The às	e Com descr	imissioner	is hereby auth A duplicate	horized to charge a copy of this sheet i	and credit D	eposit Ac	ocount No. 02-1504(IN	33)
		Charge the	e amount of	as	is enclosed filing fee.	•		
			overpayment.		~~~ 07 ([D 446		
		Sharge the	issue fee set	ing fees required ur in 37 C.F.R. 1.18 a	nder 37 C.F at the mailir	.K. 1.10 a	and 1.17. Notice of Allowance,	
	t	oursuant to	o 37 C.F.R. 1.3	311(b).	/		11.77	\wedge
					(m	Signature /	3/2
Dated:	June	3, 1998					N. Trop, Reg. No. 28,994 er, Hu & Miles, P.C.	/
		·			85	50 Katy F	Freeway, Suite 128	
					(71	13) 468-88		
cc:					(7)	13) 468-88	383 Fax	

APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE:

BINARY COMPATIBLE SOFTWARE OBJECTS

APPLICANT:

KENNETH S. KNAPTON, III

Express Mail No. ELIBS 208913US

Date Mailed: June 3,1998

Background

This invention relates generally to object oriented software technologies and particularly to software objects which are binary compatible.

- ActiveX controls are a subset of the COM object oriented software technology. COM can use a variety of different object oriented program languages such as C++, Java and Visual Basic. ActiveX controls are typically plugged into a control container which is a type of client.
- The ActiveX controls self-register on a computer in a database. In Windows®-based platforms, the database is called a registry. The registry provides a way for a control to advise the client about the control's functionality. More specifically, the ActiveX control
- 15 places keys in the registry or database to let the container know its functionality. The registry includes information which identifies a particular control or object including Globally Unique Identifiers (GUIDs), Category Identifiers (CATIDs), and Class Identifiers (CLSIDs).
- A layer class, wrapper or interface definition is a source code level version of a COM object. It provides an interface between the container or client and the object which may be an ActiveX control. Additional controls may be inserted, snapped in or "plugged in" to a container that
- 25 already has one or more controls. A plug-in control is source compatible if a new version of the control works unchanged in a container application but the user program must be rebuilt. That is, the application program must be recompiled and then the application can be run without 30 further change.

With a "binary compatible" control, a new version

can be plugged into an existing application that was designed and built for the old version. However, the conventional wisdom in the field is that the plug-in must appear to the container as if it were the old version in order for the plug-in to be binary compatible. That is, the plug-in must support the old CLSID and all interfaces exactly as they were (that is, with the same IIDs, names, dispids, parameters and so forth). See Denning, Adam, "ActiveX Controls Inside Out", Microsoft Press (1997), p. 0 131. Thus, the conventional wisdom holds that in order to

10 131. Thus, the conventional wisdom holds that in order to be binary compatible, the same identifiers and interfaces must be used for the plug-in.

A GUID is conventionally hard coded into a layer class. Other objects can then be used with a given container; however, they must have the same interface and GUID in order to work with the layer class in a binary compatible fashion.

Thus, there is a continuing need to enable objects, with different interfaces and/or different GUIDs, to snap in 20 to a container or client environment.

Summary

In accordance with one aspect of the present invention, a method for object oriented programming includes 25 creating a first object, having a first identifier associated with a first client. Thereafter, a second object having a second identifier is inserted, such that the second object is associated with the first client. Even though the first and second identifiers are different, the second 30 object is used with the first client, without recompiling.

Brief Description of the Drawings

Fig. 1 is a high level flow diagram in accordance with one aspect of the present invention;

Fig. 2 is a more detailed flow chart for
5 implementing a flow in accordance with Fig. 1; and
Fig. 3 is a conceptual depiction of an approach to object oriented programming.

Detailed Description

- Referring to Fig. 1, a method for object oriented programming may be implemented in any object oriented programming technology including COM, ActiveX, Java, Visual Basic, C++ and the like. As indicated in block 10, a first object with a first GUID is registered on the system. Then
- 15 a second object with a second GUID may be registered as indicated in block 12. Time may pass between the first and second registrations. The registration may be done in any conventional database for registering objects including the so-called registry utilized in Windows®-based platforms.
- As indicated in block 14, it is thereafter possible to selectively access one of the first and second objects using the same client or container despite the fact that the objects have different GUIDs. In addition, these first and second objects may be accessed using the same container or
- 25 client despite the fact that they have different interfaces, for example, in connection with COM based objects. Of course, the dispids and parameters for the two objects still would be the same. However, the first object or the second object may be selectively accessed after snapping in the 30 second object.

In this way, a truly binary compatible object system

may be developed in which a second object may be snapped into a container or client containing a first object and the second object may be utilized without recompiling. No recompiling is necessary even though the first and second objects have different GUIDs and even if the first and second objects have different interfaces, for example, in the case of COM applications.

While these techniques are applicable to a variety of technologies, they are particularly applicable to ActiveX 10 controls wherein first and second controls may be snapped into a container. In this way the container can selectively access either the first or the second object without recompiling. In applications using a layer class or wrapper, the layer class may then be associated with more 15 than one object. A new ActiveX control can be snapped in without creating a new layer class each time, which would require recompiling.

Referring now to Fig. 2, a more detailed flow chart for implementing the technology of Fig. 1 in COM technology 20 begins with block 16. At block 16, each object for a given client or container is registered. At block 18, a layer class is appropriately programmed (using the SetGUID and GetGUID methods described below) to enable the GUIDs for any of the registered objects to be selected. Thereafter, it is 25 then possible to access either object despite the fact that the second object that is snapped in may have a different GUID than the first object. In connection with applications involving ActiveX controls using dynamic linked libraries or DLLs, the registration is normally accomplished using the 30 DllRegisterServer() method in Windows®-based applications. In non-ActiveX applications when DLLs are not used, the

20

registration may be done with EXEs. In this way, the GUIDs of the respective objects are registered in a database (or in Windows® applications, at the registry).

SetGUID and GetGUID methods are implemented in an 5 application involving a layer class. GetGUID, which is part of the layer class, provides the GUID that is set when the layer class calls for its own GUID. The SetGUID method, which is part of the layer class, sets the GUID in the layer class for the desired object, as shown at block 22. Thus, 10 SetGUID sets the new GUID in the layer class and GetGUID returns the GUID from the database.

In alternative embodiments it is possible to use the CoCreateInstance method to send in the GUID of the second object when that object is referenced. The GUID of the second object is sent in for the snapped in second object and the same interface definition may be utilized for both objects. In this case, the SetGUID and the GetGUID method are unnecessary and manipulation of the layer class is likewise unnecessary.

Using either technique, it is possible to dynamically create new functions in the future for a given client or container. This can be done in a truly binary compatible fashion without requiring identifiers to be identical or interfaces to be identical, or recompiling.

25 Referring again to Fig. 2, one can access the first object, as indicated in block 24, thereafter obtain the GUID for a second object, as indicated in block 26, and set the GUID for the second object in place of the GUID for the first object, as indicated in block 28. As indicated in block 30, the second object may be accessed by the same container or client that previously would have accessed the

first object. This is done in a binary compatible fashion without recompiling.

These techniques are applicable, not only to in process servers such as DLLs, but also to remote

5 applications, such as Distributed COMs (DCOMs). Generally the techniques described herein are applicable to any object which can be snapped into a container or client situation.

Referring now to Fig. 3, a pair of objects 32 and 34 have different GUIDs and different interfaces. The

10 interface for the object 32 is indicated as I1 and the GUID for object 32 is indicated as GUIDA. Similarly, the GUID for object 34 is GUIDB and the interface for object 34 is I2.

The compiled application, indicated within the

15 dotted line box 36, includes, in the illustrated embodiment,
a layer class or wrapper 38 and the client or container 46.

As indicated, the layer class communicates with the client
46.

The layer class 38 includes the SetGUID method 42 20 and the GetGUID method 40. The layer class 38 also stores the selected GUID 44. In the illustrated embodiment, the selected GUID is the GUIDA as indicated by the arrow between the layer class and the object 32. However, the layer class can obtain the GUID for the object 34 through the client

25 from the system database 48. The system database or registry includes GUIDs 50 and 52 in the illustrated embodiment. Thus, the client can obtain GUIDs for desired objects from the system database 48 and the layer class can access the corresponding object without requiring 30 recompiling.

In prior systems, the objects 32 and 34 would need

to have the same GUIDs and interfaces to enable a binarily compatible snap-in system. Now snap-in objects with different GUIDs and different interfaces may be used to implement new functions as necessary in the future without 5 recompiling. In this way, a layer class may be created that has selectively programmable GUIDs for more than one object.

With embodiments of the present invention, one can extend a current technology by allowing updates and new functions. That is, a new object may be used in place of 10 its predecessor. The new object may also be used selectively in conjunction with its predecessor.

While the present invention has been described with respect to a limited number of preferred embodiments, those skilled in the art will appreciate numerous modifications

15 and variations therefrom. For example, while the illustrated embodiments illustrate a COM or ActiveX controls application, those skilled in the art will appreciate that similar approaches can be used in other programming technologies and languages. It is intended that the appended claims cover all such modifications and variations as fall within the true spirit and scope of the present invention.

What is claimed is:

- A method for object oriented programming 1 1. 2 creating a first object having a first comprising: identifier, said object associated with a first client; 3 inserting a second object having a second 4 identifier, said second object associated with the first 5 client, said first and second identifiers being different; 6 7 and using said second object with said first client 8 9 in place of the first object without recompiling
- The method of claim 1 including creating a 2. 1 2 first COM object having a first globally unique identifier, said first COM object associated with a first container, 3 inserting a second COM object having a second globally 4 unique identifier, said second COM object associated with 5 the first container, the first and second globally unique 6 identifiers being different, and using said second COM 7 object with the first container without recompiling. 8
- 3. The method of claim 2 including providing a
 layer class and setting said globally unique identifier in
 said layer class.
- 1 4. The method of claim 1 including creating a 2 layer class that interfaces with one of a plurality of 3 globally unique identifiers of objects associated with said 4 layer class.
- 5. The method of claim 1 including using said first object again with said first client in place of said

- 3 second object without recompiling.
- 1 6. A method for object oriented programming
- 2 comprising:
- 3 registering a first object with a first
- 4 globally unique identifier;
- 5 registering a second object with a second
- 6 globally unique identifier; and
- 7 selectively accessing one of said first and
- 8 second objects without recompiling.
- 1 7. The method of claim 6 including creating a
- 2 source code version of said objects, and programming said
- 3 globally unique identifiers into a layer class.
- 1 8. The method of claim 7 including getting the
- 2 globally unique identifier for each object from a database
- 3 and setting each globally unique identifier in said layer
- 4 class.
- 1 9. A container for a software object comprising:
- one or more objects, said container adapted to
- 3 selectively work with first and second objects having
- 4 different identifiers.
- 1 10. The container of claim 9 including a layer
- 2 class adapted to selectively utilize the identifier of
- 3 either said first or second object.
- 1 11. The container of claim 10 wherein said layer
- 2 class includes a first function that obtains globally unique

- 3 identifiers from a system database and a second function
- 4 that sets globally unique identifiers in the layer class.
- 1 12. A computer readable storage medium for storing
- 2 a program including instructions for causing a computer to:
- 3 create an object having a first identifier,
- 4 said object associated with a first client;
- 5 insert a second object having a second
- 6 identifier, said second object associated with the first
- 7 client, said first and second identifiers being different;
- 8 and
- 9 use said second object with said first client
- 10 in place of said first object without recompiling.
 - 1 13. The medium of claim 12 wherein said objects are
 - 2 COM objects.
 - 1 14. The medium of claim 13 wherein said COM objects
 - 2 are ActiveX controls.
 - 1 15. The medium of claim 13 wherein said identifiers
 - 2 are globally unique identifiers.
 - 1 16. The medium of claim 15 including one or more
 - 2 instructions for storing a program instructions for causing
 - 3 a computer to create a layer class having selectively
 - 4 programmable globally unique identifiers for more than one
 - 5 object.
 - 1 17. The medium of claim 16 including instructions
 - 2 for causing a computer to obtain globally unique identifiers
 - 3 and setting the identifiers in the layer class.

5

10

15

BINARY COMPATIBLE SOFTWARE OBJECTS Abstract

An object oriented programming technology enables multiple objects to be snapped into a given container or client. Thus, for example, multiple ActiveX controls can be snapped into one given container and these controls may be accessed in a fashion which can be truly termed binary compatible. That is, each of the controls can be accessed without requiring recompiling even when they have different identifiers and/or different interfaces. In one embodiment, this may be accomplished by providing SetGUID and GetGUID functions in a layer class associated with the objects. The identifier of the desired object can be obtained from the system database and set in the layer class to selectively access one of at least two objects in the same container without recompiling.






Figure 1





DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION (FOR INTEL CORPORATION PATENT APPLICATIONS)

As a below named inventor, I hereby declare that:

Attorney's Docket No.: INTL-0033-US (P5395)

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

BINARY COMPATIBLE SOFTWARE OBJECTS

the specification of which

X	is attached hereto.		
	was filed on	As	
	United States A	pplication Number	
	or PCT Internati	onal Application Number	
	and was amend	ed on	
		(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate Issued before the date of this application in any country foreign to the United States of American on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign App	olication(s):		Priority Ci	aimed
Number	(Country)	(Day/Month/Year Filed)	Yes	No
Number	(Country)	(Day/Month/Year Filed)	Yes	No
Number	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under titl States provisional application(s) list		Code, Section 119(e) of the United
(Application Number)		(Filing Date)
(Application Number)		(Filing Date)
States application(s) listed below a of this application is not disclosed provided by the first paragraph acknowledge the duty to disclose patentability as defined in Title 3	and, insofar as the s d in the prior United of Title 35, Unit se all information 37, Code of Federa ng date of the prior a	es Code, Section 120 of any United subject matter of each of the claims of States application in the manner ed States Code, Section 112, I known to me to be material to all regulations, Section 1.56 which application and the national or PCT
(Application Number)	Filing Date	(Status-patented, pending, abandoned)
(Application Number)	Filing Date	(Status-patented, pending, abandoned)

I hereby appoint Timothy N. Trop, Reg. No. 28,994; Fred G. Pruner, Jr., Reg. No. 40,779, Dan C. Hu, 40,025; Coe F. Miles, Reg. No. 38,559, my patent attorneys, of TROP, PRUNER, HU & MILES, P.C., with offices located at 8550 Katy Freeway, Ste. 128, Houston, TX 77024, telephone (713) 468-8880, and Joseph R. Bond, Reg. No. 36,458; Richard C. Calderwood, Reg. No. 35,468; Sean Fitzgerald, Reg. No. 32,027; David J. Kaplan, Reg. No. 41,105; Leo V. Novakoski, Reg. No. 37,198; Naomi Obinata, Reg. No. 39,320; Thomas C. Reynolds, Reg. No. 32,488; Steven P. Skabrat, Reg. No. 36,279; Howard A. Skaist, Reg. No. 36,008; Steven C. Stewart, Reg. No. 33,555; Raymond J. Werner, Reg. No. 34,752; and Charles K. Young, Reg. No. 39,425; my patent attorneys, of INTEL CORPORATION; with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

Send correspondence to <u>Timothy N. Trop</u>, TROP, PRUNER, HU & MILES, P.C., 8550 Katy Freeway, Ste. 128, Houston, TX 77024 and direct telephone calls to <u>Timothy N. Trop</u>, (713) 468-8880.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor:	
Kenneth S. Knapton, III	
Inventor's Signature?	Date:
Thut I four as	6-1-98
Residence: 1239 N 200 W, Orem, UT 84057	Citizenship: USA
Post Office Address: 1239 N 200 W, Orem, UT 84057	

INTL-0039-US